

## S29911

25T5/LED/46-850/DR 25 watt T5 LED; Miniature bi-pin base; 5000K; 50000 Average rated hours; 3500 lumens

## Features

- Direct Replacement for use on Electronic ballasts with no rewiring required\*
- Replaces F54T5/HO linear fluorescent lamps
- High efficacyNSF Approved
- Integrated thermal fuse at pins
  5 year Limited warranty

\*May not be compatible with all rapid start ballasts.

Ballast required

View: **Ballast Compatibility Chart** 

=	SSATCO" 2011/LEOH-MINIOR Coupling in maturalitat 204 2000LB 522811	e anno anno
	S29	911
	S29	911

Item Number	l	UPC	Wat	ts	Fluorescent Equivalent		.amp Shape	l	Base	ANS Bas		L	.amp	Code
S29911	04592	232991	17 25		54W		T5	Mini	ature Bi- Pin	G	5	25T5/I	LED/	46-850/DR
Finish	MOL In	Inches	Initial Lu	nens	Average Rated H	ours	Kelvin T	Гетр	Co	olor	CF	RI Bea	am S	pread Deg
Gloss White	48	3''	3500	)	50000		500	0	Natura	al Light	82	2		185
Operatir Tempera	9	Pack	CEC Sta	us	DLC ID:	С	RoHS Compliant	Ī	JL or ETL .isted	UL CI	assifi	cation		Warranty
-20C (-4F) maximum of (+113F	+45C	10	Lawful for a in Califor		PL2M6895FL33 DLC Search		Yes		Yes	cULus Damp Lo				<u>5 Year</u> Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051